

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2002-088228

(43)Date of publication of application : 27.03.2002

(51)Int.Cl.

C08L 63/00

C08K 3/00

C08L 35/04

G02F 1/1339

(21)Application number : 2000-279329

(71)Applicant : MITSUI CHEMICALS INC

(22)Date of filing : 14.09.2000

(72)Inventor : KITAMURA TADASHI

MIZUTA YASUSHI

KONDO HIROSHI

NAGATA KATSURA

MAEDA SUNAO

(54) SEALANT COMPOSITION FOR LIQUID CRYSTAL DISPLAY ELEMENT AND PRODUCTION PROCESS OF LIQUID CRYSTAL DISPLAY ELEMENT**(57)Abstract:**

PROBLEM TO BE SOLVED: To provide a sealant composition for liquid crystal display elements which is excellent in adhesion to a nematic liquid crystal surface, can shorten the production process by thermally curing the composition simultaneously with the sealing of a nematic liquid crystal, and gives a liquid crystal cell which is rich in reliability of adhesion to a cell-constituting substrate, can exhibit a homogenous liquid crystal display function, and is excellent in long-time (longer than 1,000 h) seal reliability and durability of liquid crystal display function under high-humidity high-temperature conditions of 60° C/saturated humidity of 95%.

SOLUTION: This sealant composition comprises (1) 20-83.99 mass% epoxy resin, (2) 10-35 mass% latent epoxy-curing agent, (3) 5-50 mass% inorganic filler, (4) 1-20 mass% fine hydrophilic polymer particles having a solubility parameter (SP value) of 11.1-15 (cal/cm³)^{1/2}, and 0.01-5 mass% cure accelerator.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]